

Impressora sublimática A-1602TX/ 1802TX

ESPECIFICAÇÕES TÉCNICAS

1,60 / 1,80 m



INKJET



Panda
UV Printers

MODEL	A-1602TX	A-1802TX
Print Head	Dual i3200 Print Heads	
Printing Technology	Piezoelectric Inkjet	
Acceptable Media	Width	63.8 in.(1620 mm) / 71.6 in.(1820 mm)
	Thickness	Maximum 39 mil(1 mm)
	Weight	132.2 lb.(60 kg)
Printing Width	63 in.(1600 mm)	70.8 in.(1800 mm)
Ink Cartridges	Type	Sublimation Ink
	Capacity	4*4 CISS (220ml ink cartridge with 1.5L ink tank)
	Color	4 colors (Cyan, Magenta, Yellow, Black)
Printing Resolution	Maximum 3600 dpi	
Printing Speed	4pass(720x1200dpi): 40sqm/h	
	6pass(720x1800dpi): 27 sqm/h	
Media Heating System	Intergrated post heater & Infrared Dryer & Fan system	
Interface	LAN	
Power Supply	AC 220V ± 10%, 50/60 HZ	
Dimensions(with stand)	102(W)x27(D)x61(H) in.	108(W)x 31(D)x61(H) in.
	2600(W)x680(D)x1550(H) mm	2800(W)x780(D)x1550(H) mm
Weight(with stand)	240 kg	280 kg
Package Dimensions	106(W)x30(D)x30(H) in.	114(W)x30(D)x30(H) in.
	2700(W)x760(D)x760(H) mm	2900(W)*760(D)*760mm(H)mm
Package Weight	260 kg	300 kg
Environment	Power on	Temperature: 59 F to 90 F [15C to 32 C] (68 F [20 C] / Humidity: 35 to 80% (no condensation)
	Power off	Temperature: 41 F to 104 F [5C to 40 C] / Humidity: 20 to 80% (no condensation)
Accessories	Print Heads, USB cable, media clamp, manual, drain bottle, ink cartridges, RIP software, etc.	



FALE CONOSCO

19 9 7413 3945
11 4028 7100



Panda
UV Printers